

Construction	Diameter	Weight		Nominal B.S.(Lbs)	
	inch	lb/100ft	kg/100m	AISI304	AISI316
7*19(6*19+IWS)	5/64	1.14	1.70	650	560
	3/32	1.74	2.59	920	810
	1/8	2.90	4.32	1760	1530
	5/32	4.50	6.70	2400	2110
	7/32	8.60	12.80	5000	4350
	1/4	11.00	16.37	6400	5600
	9/32	13.90	20.68	7800	6800
	5/16	17.30	25.74	9000	8200
	3/8	24.30	36.16	12000	11000
	1/2	46.00	68.45	22800	20700
	9/16	59.00	87.80	28500	26000

Construction	Diameter	Weight		Nominal B.S.(Lbs)	
	inch	lb/100ft	kg/100m	AISI304	AISI316
6*19S+IWS	9/32	15	22	7290	6640
	5/16	18	27	9000	8200
	3/18	26	39	12000	10800
	7/16	35	52	16300	14800
	1/2	46	68	22800	20500
	9/16	59	88	28500	25700
	5/8	72	107	35000	31500
	11/16	87	129	41680	37480
	3/4	104	155	49600	44600
	7/8	142	211	66500	59900
	15/16	163	243	75060	67590